

# WORK PLATFORMS

Includes utility frame with fixed, non-folding rails and features a number of features designed with safety in mind. Meets and exceeds ANSI/ITSDF B56.6 standards for elevated platforms.

## FOR APPLICATIONS WITH:

- Telescopic Material Handlers
- Rough Terrain Forklifts
- Warehousing and In-plant Forklifts



Model	Size	Fork Spread	Occupancy
WP48-48-FL	48" x 48"	36"	2 people
WP48-72-FL	48" x 72"	48"	4 people
WP48-96-FL	48" x 96"	48"	4 people
WP48-116-FL	48" x 116"	48"	4 people

## WORK PLATFORM FEATURES:

- Fork pockets accept forks up to 2 3/4" thick and 6" wide, but fork lengths must be 42" to 48"
- Fork pockets are spaced 48", except on WP48-48-FL which are spaced 36"
- Heavy duty 1 1/4" square tubing that exceeds the 225 lb. capacity requirement
- Top rail is located at 42" height and toe board height is 6" tall
- Heavy duty expanded metal floor, covered with non-slip rubber mat
- Includes a Work Safe Booklet, which helps users understand the OSHA rules and regulations regarding proper use of Work Platforms, and provides checklists to help you or your company comply with use
- Steel pins secure frame behind heel of forks and includes safety retaining chain
- Gates, located at both ends, are swing in and latchable and include safety stops
- OPTIONAL Mast Guard - mast protection screens are available and must be added when used on trucks with vertical mast or backstop area poses a safety hazard. Standard Mast Guard size is 42" x 72"
- SPECIALTY Utility Pole model (WP48-72CO) - includes 24" square cutout to allow access to 3 sides of poles

For low and high lift industrial trucks (forklifts): ITSDF B56.6-2016, paragraph 7.38.3(e) reads, "floor dimensions that neither exceed two times the load center distance listed on the truck nameplate, measured parallel to the longitudinal center plane of the truck, nor have a width greater than the overall width of the truck (measured across the load bearing tires) plus 250 mm on either side." Visit [www.itsdf.org](http://www.itsdf.org) for the complete ITSDF B56 safety standards.

ASWP17188



800-821-7563

16000 W. 108th Street, Lenexa, KS 66219  
Phone: (913) 495-4800 • FAX: (913) 227-0523  
Email: [sales@ArrowMHP.com](mailto:sales@ArrowMHP.com)  
Website: [ArrowMHP.com](http://ArrowMHP.com)